




BC-100 II Boundary Microphone Base

Features

- Equipped with a high-sensitivity condenser capsule module, it can be used directly as a boundary microphone.
- Compatible with MM series 4-pin gooseneck microphones, offering both wired and wireless transmission options.
- For wired transmission, connect the base output to a mixer input with phantom power.
- For wireless transmission, it supports ACT-TC series bodypack transmitters, converting it into a wireless conference microphone with direct charging capability, eliminating the need to remove the transmitter.
- Includes TALK and MUTE buttons to control the base indicator light and sync with the LED ring lights of MM-206L, MM-205L, and MM-204L microphones.
- Features a metal base and non-slip pad for stability and to prevent wobbling.



Specifications

Boundary Microphone	10 mm cardioid condenser microphone capsule module
Output Jack	3-Pin XLR
Input Jack	MIPRO 4-Pin XLR, compatible with MM-206L / MM-205L / MM-204L gooseneck microphone
Control Button	TALK / MUTE button with LED indicator
Expansion Function	Insert an ACT-TC series bodypack transmitter for wireless transmission
Power Supply	Wired: DC 24 – 48 V phantom power Wireless: one 18500 Li-ion battery
Charging Voltage	DC 5 V / 1 A
Color	Black
Dimensions	100 × 78 × 150 mm (W × H × D)
Weight	Approx. 620 g